



The World's Sixth Sense®

Pan/Tilt/Zoom Cameras Supported by IOI Analytics

May 2017

Manufacturer	Type	Model	Autonomous PTZ tracking	Analytics on PTZ presets	Comments
FLIR	Dome	DNZ30TL2R		√	Analog connection
	Dome	CP-4221-20X (PAL/NTSC)		√	IP connection with Latitude
	Dome	CP-4221-30X (PAL/NTSC)	√	√	IP connection with Latitude. Requires camera with HW Revision 2 or 3. Camera must be at minimum 6m/20ft. height.
Pelco	Spectra III	DD53CBW-X (zoom x23 PAL)	√	√	
		DD53CBW (zoom x23 NTSC)	√	√	Contact FLIR ¹
		DD53C22 (zoom x22 NTSC)	√	√	Contact FLIR ¹
		SD53C22 (zoom x22 NTSC)	√	√	Contact FLIR ¹
		DD53TC16 (zoom x16 NTSC)	√	√	Contact FLIR ¹
		SD53TC16 (zoom x16 NTSC)	√	√	Contact FLIR ¹
	Spectra IV	Zoom x35 (PAL/NTSC)	√	√	FW 1.08, 2.1.1
		DD4CBW35 Zoom x18/x23/x35 PAL/NTSC)	√	√	FW 1.08
Esprit	ESIOPCBW18-X (zoom x22/x23 PAL/NTSC)	√	√	Contact FLIR ¹	
Bosch	G3A/ EnviroDome	ENVT 120/230 P/R/W/M/C/P {F} {T} zoom x25 (PAL/NTSC) ²	√	√	Contact FLIR ¹
Samsung (Techwin)	Speed Dome	SPD 3300 zoom x30 (PAL/NTSC)	√	√	
		SPD 3750 zoom x37 (PAL/NTSC)	√	√	
Samsung (Electronics)	Smart Dome	SCC - C6405 zoom x22 (PAL/NTSC)	√	√	Contact FLIR ¹ Motor FW 0.027/1.003/1.006 Detection and handoff from a fixed camera not supported. Zoom speed must be set to -2.
		GOP zoom x20 (PAL/NTSC)	√	√	
		Robot zoom x30 (PAL/NTSC)	√	√	
Panasonic		WV-CS950 x22 (PAL/NTSC)	√	√	
		WV-CW590 zoom x36 (NTSC)	√	√	
		WV-CW960 zoom x30 (NTSC)	√	√	
Honeywell	Scandome III	HSDC-251NX – zoom x25 (PAL/NTSC)	√	√	
		HSDC-351N – zoom x35 (PAL/NTSC)	√	√	
SONY	IPELA	SNC-RZ50 zoom x26 (PAL/NTSC)	√	√	
NEC		PT103 zoom x20 (PAL/NTSC)	√	√	Contact FLIR ¹
World-CCTV	Smart Dome	IVS – zoom x26 (PAL/NTSC)	√	√	FW: 3.6.1
Generic		All cameras supporting PELCO-D or VCL protocol		√	For use with PTZ cameras not integrated and tested in FLIR labs.

Notes: ¹ Contact FLIR to confirm support. ² Slash "/" means one of the listed. Parenthesis "{" means optional extension.

FLIR Systems, Inc. 6769 Hollister Ave. Goleta, CA 93117
 Tel: +1 888.388.3577 Fax: +1 805.685.2711
 product.enterprise.support@flir.com www.flir.com/security